



# Effect of *Rhizobium* Coating on Physical and Engineering Properties of Chickpea Seed

Raghavendra Veerammanavara <sup>a++\*</sup>, Prakash K. V. <sup>a#</sup>,  
H. Manjunath <sup>a++</sup>, Siddesh Marihonnappanavara <sup>b†</sup>,  
Mareppa H. <sup>c++</sup>, Murali M. <sup>c++</sup>, Santosh <sup>c‡</sup>  
and Vinayaka Niranjana <sup>d^</sup>

<sup>a</sup> Department of Renewable Energy Engineering, College of Agricultural Engineering, Raichur, India.

<sup>b</sup> Farm Machinery Testing Centre, CAE, Raichur, India.

<sup>c</sup> Department of Farm Machinery and Power Engineering, College of Agricultural Engineering, Raichur, India.

<sup>d</sup> K.H. Patil KVK, Hulkoti, India.

## Authors' contributions

This work was carried out in collaboration among all authors. All authors read and approved the final manuscript.

## Article Information

DOI: 10.9734/IJECC/2023/v13i102885

## Open Peer Review History:

This journal follows the Advanced Open Peer Review policy. Identity of the Reviewers, Editor(s) and additional Reviewers, peer review comments, different versions of the manuscript, comments of the editors, etc are available here: <https://www.sdiarticle5.com/review-history/104991>

Original Research Article

Received: 20/06/2023

Accepted: 25/08/2023

Published: 05/09/2023

## ABSTRACT

The *Rhizobium* bio fertilizer coating may influence on the physical and engineering properties of chickpea seed. The metering mechanism, hopper design and hose pipes of seed drill was designed based up on the physical and engineering properties of *Rhizobium* coated seeds. The study was

<sup>++</sup> Assistant Professor;

<sup>#</sup> Professor;

<sup>†</sup> Testing Engineer;

<sup>‡</sup> Ph.D Scholar;

<sup>^</sup> Subject Matter Specialist;

\*Corresponding author: E-mail: raghuv44@gmail.com;

conducted to determine the physical and engineering properties viz., length, breadth, thickness, geometric mean diameter, sphericity, seed weight, bulk density, angle of repose and coefficient of static friction of uncoated, and bio-fertilizer coated chickpea seeds for design of Aqu-ferti seed drill. The hopper of seed drill was designed based up on the angle of repose and coefficient of static friction of biofertilizer coated chickpea seeds. The physical properties of chickpea seeds plays very important role in design of hopper, hose pipe and metering mechanism of seed drill. The physical properties viz., Length, breadth and thickness of the uncoated and bio-fertilizer coated chickpea seeds were  $9.01\pm 0.62$  mm,  $7.059\pm 0.69$  mm,  $6.57\pm 0.54$  mm and  $9.06\pm 0.44$  mm,  $7.144\pm 0.90$  mm,  $6.9\pm 0.22$  mm, respectively. Roundness and sphericity of uncoated and bio-fertilizers coated chickpea seeds were  $87.23 \pm 2.13\%$ ,  $87.36\pm 2.72\%$  and  $81.6\pm 3.07\%$ ,  $82\pm 4.15\%$ , respectively. Bulk density of uncoated and bio fertilizer coated seeds were  $0.629\pm 0.02$  g/cc and  $0.641\pm 0.03$  g/cc, respectively. Geometric mean diameters of uncoated and coated seeds were  $7.32\pm 0.45$  mm and  $7.33\pm 0.45$  mm, respectively. The hopper of seed drill was designed based up on the angle of repose of mild steel which influences on free flow of seeds. The angle of repose for mild steel surface was observed as  $26.9\pm 5.61$  and  $29.51\pm 4.23$  degree for uncoated and bio-fertilizer coated chickpea seeds, respectively.

**Keywords:** Angle of repose; bulk density; geometric mean diameter; sphericity; static coefficient of friction.

## 1. INTRODUCTION

India is one of the major pulses growing country of the world, accounting roughly for one third of total world area under pulse cultivation and one fourth of total world production. Pulses occupy a key position in Indian diet and meet about 30 per cent of the daily protein requirement. Among the pulses; chickpea is a most important one [1]. Chickpea is an important winter season pulse crop in India grown as a dry pulse crop or as a green vegetable with the former use being most common. It ranks first in area cultivated in India, grown over an area of 8.11 million hectares with production of 5.9 million tones with average productivity of 727 kg/ha [2]. India contributes 75% of the total world production of chickpea followed by Turkey and Pakistan. India grows chickpea on about 6.67 million ha area producing 5.3 million tonnes which represents 30% and 38% of the national pulse acreage and production, respectively. India is major producer of chickpea but productivity is very low as compared to other chickpea producing countries. India is also major importer of chickpea because of more consumption. So there is urgent need to increase the productivity of chickpea. Now a day's higher usage of chemical fertilizer leads to deterioration of soil health. The bio-fertilizers are soil friendly it will provide soil nutrient without deteriorating the soil health. So, Mechanisation is needed for increasing the productivity of chickpea. Efficient seeding depends on accuracy, precision and uniformity of seed placement. Indian farms have been traditionally sown by using manual and bullock drawn

seeder. The most popular traditional methods of sowing like broadcasting, line sowing behind the plough. Mechanization improves precision, effectiveness, timeliness of operation and it is economical as well. The physical proprieties of seeds are important factors which determine the design values of metering mechanism. Hence study was undertaken to determine the physical properties of chickpea seed. Laxmikath et al. [3], conducted to investigate physical properties of chickpea seeds at different levels of moisture content 16.41-25.65% (d.b.). The average value of length, width and thickness varied from 8.27-9.39 mm, 6.16-7.02 mm and 5.59-6.62 mm, respectively. Geometric mean diameter and sphericity varied 6.57-7.58 mm and 79.55– 80.77 percent, respectively. Average value of bulk density and true density varied from 722.02 to 689.05 kg m<sup>-3</sup> and 875.09 to 850.51 kg m<sup>-3</sup> respectively. The angle of repose ranged between 22.34 to 25.52°. The roundness of chickpea ranged between 0.77 to 0.80, seed weight 230.81 to 248.11 respectively. Davies [4] studied the engineering properties of three different varieties of melon seeds and four frictional surfaces were used, namely, glass, plywood, galvanized steel and concrete for determination of static friction and angle of repose and reported that the highest coefficient of friction was observed in concrete surface for all the three varieties of melon investigated. Karaj et al. [5] .determined the engineering properties of *Jatropha curcas* seeds. It was reported that coefficient of static friction of seeds was higher on rubber surface and lowest on stainless steel. The coefficient of static friction

was observed higher on all surfaces for kernels than for seeds. It was found that angle of repose of kernels was higher than for seeds. Mollazade et al. [6]. determined the some of engineering properties of cumin seed. Three surfaces were used for determination of engineering properties *i.e.*, glass, galvanized iron sheet and plywood. It was reported that the static angle of repose (43-49 deg), dynamic angle of repose (47-56.6 deg) and coefficient of static friction on the three surfaces: glass (0.48-0.77), galvanized iron sheet (0.36-0.73), and plywood (0.57-0.69). Sinha et al. [7]. studied the physical and engineering properties of 20 chickpea seeds such as length, width, thickness, sphericity, aspect ratio, geometric mean diameter, thousand seed weight, bulk density and moisture content. The average length, width, thickness, sphericity, aspect ratio, geometric mean diameter, thousand seed weight, bulk density and angle of repose are 8.48 mm, 6.45 mm, 6.03 mm, 0.81, 75.54 %, 6.90 mm, 244.85 g, 709.55 kg/m<sup>3</sup> and 19.81 % respectively. This study is useful for design of metering mechanism for chickpea seeds.

## 2. MATERIALS AND METHODS

Physical and engineering properties were determined in the laboratory of Division of Agricultural Engineering, IARI New Delhi. The chickpea crop variety BG 1003 was selected for laboratory testing and field experiment. The relevant properties of chickpea seeds were measured for coated and uncoated seeds. Experiments are carried out at two levels namely uncoated seed (S<sub>1</sub>) and bio-fertilizer coated seed (S<sub>2</sub>). *Rhizobium* bio-fertilizer coating was done taking sugar solution as adhesive for bio-fertilizer. Size of seed in terms of length, breadth and thickness were measured using digital vernier calliper. Twenty seeds were randomly selected from bulk and subjected for size analysis with three replications.

The shape of the chickpea seed was reckoned as roundness and sphericity. The geometric mean diameter (D<sub>g</sub>), arithmetic mean diameter (D<sub>a</sub>) mm, roundness % and sphericity of the seeds were computed by following equations [3].

$$D_g = (abc)^{1/3}$$

$$D_a = \frac{(a+b+c)}{3}$$

$$\emptyset = \frac{(abc)^{1/3}}{a}$$

Where

a = Length, b = Breadth and c = Thickness

D<sub>g</sub> = Geometric mean diameter,

D<sub>a</sub> = Arithmetic mean diameter and

∅=Sphericity

An empty container (150mL) was weighed using a digital balance to the nearest 0.0001g. The container was filled with a sample and the material was slightly compacted to ensure absence of large void spaces. The container and the sample were then weighed. Ten replications were carried out *et al.* [3]. The bulk density of sample was calculated from the following given equation.

$$BD=M/V$$

Where,

BD = Bulk density, g/cm<sup>3</sup>

W = Weight of seed, g

V= Volume of cylinder, cm<sup>3</sup>

The apparatus used for measuring dynamic angle of repose consisted of a funnel with an adjustable throat opening mounted on a stand. A circular plate, with two centring arms, was mounted in the funnel below the adjustable throat. The funnel was filled with seeds by keeping its adjustable throat closed. The throat was fully opened to allow free flow of seeds over and around the plate mounted beneath the funnel. At the end of process, a heap-cone of the seed was formed on the plate. From the heap cone, base diameter and height of cone were measured [3]. The angle of repose was calculated with the following relationship:

$$\emptyset = \tan^{-1} \left( \frac{h}{r} \right)$$

Where,

∅ = Angle of repose, degrees

h = Height of cone, cm

r = Radius of heap, cm

The coefficient of static friction of two surfaces *i.e.*, aluminum and mild steel were measured for the seed by using inclined plane method. The material was kept on a horizontally placed surface and the slope was increased gradually. The angle (α) at impending slide was recorded. The coefficient of static friction was expressed by tanα. The procedure was repeated 20 times and the mean value was calculated. The experiment was conducted for all the levels of test variables as shown in Table 1.

**Table 1. Seed properties and levels of test variables**

Sl. No.	Properties	Test variables	Levels of test variables
1	Size	Chickpea seeds	S1 –Uncoated seed
2	Shape		S2-Bio-fertilizer coated seed
3	Bulk density and True density		
4	Angle of repose		
5	Coefficient of static friction	*Two surfaces	*Aluminum and mild steel

### 3. RESULTS AND DISCUSSION

The effect of *Rhizobium* coating on physical and engineering properties of chickpea seed was studied and results are presented in below.

#### 3.1 Physical Properties

The physical properties of chickpea like size (length, breadth and thickness) and shape of the seed was measured and determined by following standard procedures and explained in below.

#### 3.2 Size of the Seed

The size of the seed specified the spatial dimensions are given in Table 3. The mean length, breadth and thickness of uncoated and bio-fertilizer coated chickpea seeds was observed  $9.01\pm 0.62$  mm,  $7.059\pm 0.69$  mm,  $6.57\pm 0.54$  mm and  $9.06\pm 0.44$  mm,  $7.144\pm 0.90$  mm,  $6.9\pm 0.22$  mm, respectively. Both mean length and breadth thickness of coated seeds is slightly higher as compared to uncoated chickpea seed. However, the differences between coated and uncoated were found non-significant. These values are agreement with Tavakoli et al. [8].

#### 3.3 Shape of the Seed

The shape of the seed, in terms of roundness and sphericity are presented in Table 2. The sphericity and roundness of the chickpea seed at different levels were found in the range of 82-84 % and 85-87 %, respectively. The roundness

and sphericity of uncoated and bio-fertilizers coated chickpea seeds found to be  $87.23 \pm 2.13$  %,  $87.36\pm 2.72$  % and  $81.6\pm 3.07$  %,  $82\pm 4.15$  %, respectively. There is no significant difference was observed in sphericity and roundness for two levels of chickpea seeds but the variations were marginal. These values are agreement with Salah Ghamari et al. [9].

#### 3.4 Bulk Density and True Density of Seed

The average bulk density of the seeds for uncoated and bio-fertilizer coated chickpea seeds was observed as  $0.629$  g/cm<sup>3</sup> and  $0.641$  g/cm<sup>3</sup>, respectively. The average bulk density of seeds for uncoated and bio-fertilizer coated chickpea as shown in Table 2. The average bulk density of bio fertilizer coated seeds was higher as compared to uncoated seeds. However, it was found statistically non significant. These values are agreed with Laxmikath et al. [3]

#### 3.5 Thousand Seed Weight

The mean value of the thousand seed weight of uncoated and bio-fertilizer coated chickpeas seeds as shown in Table 5. The mean value of the thousand seed weight of uncoated and bio-fertilizer coated chickpeas seeds were found to be 236.65 g and 237.25 g, respectively. The thousand seed weight of bio-fertiliser was slightly higher than uncoated chickpea seeds. The differences were subtle as statistically non significant. These values are agreed with Sinha et al. [7].

**Table 2. Physical and engineering properties of chickpea seeds**

Parameters	Level of test variables	
	Uncoated	Coated
Length (mm)	$9.017 \pm 0.62$	$9.065 \pm 0.44$
Breadth (mm)	$7.059\pm 0.69$	$7.144\pm 0.90$
Thickness (mm)	$6.57\pm 0.54$	$6.9\pm 0.22$
GMD (mm)	$7.324\pm 0.45$	$7.32\pm 0.45$
Sphericity (%)	$81.6\pm 3.07$	$82\pm 4.15$
Roundness (%)	$87.23 \pm 2.13$	$87.36\pm 2.72$
Bulk density (g/cm <sup>3</sup> )	$0.629\pm 0.02$	$0.641\pm 0.03$
Seed weight (1000)	$236.5\pm 2.32$	$237.25\pm 3.22$
Angle of repose	$26.9\pm 5.61$	$22.75\pm 4.9$
Coefficient of friction	$0.603\pm 0.12$	$0.576\pm 4.9$

**Table 3. Size of chickpea seed at level of coated**

Seeds	Uncoated	Bio-fertilizer coated
<b>Length (mm)</b>		
Range	8.55-9.75	8.47-9.53
Mean	9.017	9.065
C.V (%)	5.34	3.96
<b>Breadth</b>		
Range	6.36-7.83	6.58-7.89
Mean	7.059	9.065
C.V (%)	7.06	3.96
<b>Thickness</b>		
Range	5.36-7.17	6.58-7.89
Mean	6.57	7.144
C.V (%)	10.20	5.48

**Table 4. Engineering properties of chickpea seed**

Seeds	Uncoated		Bio fertilizer coated	
	MS	Al	MS	Al
<b>Angle of repose</b>				
Range	23-34	22-29	23-34	22-28
Mean	29.6	24.4	26.9	24.38
C.V (%)	14.17	10.53	14.17	9.48
<b>Bulk density (g/cc)</b>				
Range	0.595-0.655		0.622-0.678	
Mean	0.629		0.641	
C.V (%)	2.87		2.57	

*C.V Coefficient of Variation (%)*

**Table 5. Angle of static friction and 1000 seed weight of uncoated and coated seed**

Seeds	Uncoated		Bio fertilizer coated seed	
<b>1000 seed weight(g)</b>				
Range	234.5-239		231-240.52	
Mean	236.65		237.254	
C.V (%)	0.697		1.17	
<b>Angle of static friction</b>				
	MS	Al	MS	Al
Range	0.344-0.754	0.424-0.674	0.364-0.687	0.249-0.547
Mean	0.603	0.509	0.576	0.392
C.V (%)	19.98	16.21	17.53	27.42

### 3.6 Angle of Repose and Coefficient of Static Friction

The angle of repose and coefficient of static friction for uncoated and bio fertilizer coated chickpea seeds as shown in Table 4 and 5. The angle of repose for uncoated seed was significant difference with coated seed. The mean value of angle of repose for uncoated and bio fertilizer coated seeds found to be 29.6 and 26.9, respectively. The highest value of angle of repose was observed as 29.6 for uncoated with the mild steel surface. For the aluminium surface, mean values of coefficient of static friction for uncoated and bio-fertilizer coated seeds was observed as 0.60 and 0.392,

respectively. The highest value for coefficient of static friction was recorded for mild steel surface for uncoated seed. However, significant difference was observed in angle of repose between uncoated and coated seed. It might be due to change in surface texture of coated seed. Hence, the angle of repose has to be considered for proper designing the hopper to free flow of seed. It imparts that it is necessary to modify hopper of exiting machine for coated seed handling. The mean weight of bio fertilizer coated chickpea seeds slightly increased as compared with uncoated seeds. The highest value of angle of repose was observed as 34 for uncoated seed for mild steel. Therefore, considering the ease and economy of

**Table 6. ANOVA table for Independent samples test for chickpea seed dimensions**

Seed Dimensions	Comparison between treatments	T-Test for Equality of Means			
		t-value	DF	Sig	Std. Error Difference
<b>(2-tailed)</b>					
length	T <sub>1</sub> -T <sub>2</sub>	-0.253	18	0.803	0.19004
Breadth	T <sub>1</sub> -T <sub>2</sub>	-0.424	18	0.677	0.20055
Thickness	T <sub>1</sub> -T <sub>2</sub>	-1.570	18	0.134	0.21973
Geometric mean diameter	T <sub>1</sub> -T <sub>2</sub>	0.000	18	1.000	0.14916
Angle of Repose	T <sub>1</sub> -T <sub>2</sub>	2.073	18	0.047	2.00146
1000 seed weight	T <sub>1</sub> -T <sub>2</sub>	-0.590	18	0.563	1.02421
Sphericity	T <sub>1</sub> -T <sub>2</sub>	-0.841	18	0.412	1.21936

T<sub>1</sub>= Uncoated Chickpea Seed; T<sub>2</sub>= Bio-Fertilizer Coated Chickpea Seed

fabrication, the mild steel surface was selected for the experiment.

The statistical analysis was conducted with T-test method in different levels of parameters were used for the experiment as shown in Table 6. The parameters are length, breadth, thickness, geometric mean diameter, 1000 seed weight and sphericity was found to be non significant at 5 per cent level of significance and the angle of repose was found to be significant at 5 per cent level of significance.

#### 4. CONCLUSION

The study well evaluated the effect of rhizobium coating on physical and engineering properties of chickpea seed. The physical proprieties of seeds are important factors which determine the design values of metering mechanism. Chickpea productivity must be increased through mechanisation. The accuracy, precision, and uniformity of seed placement are critical for efficient seeding. This study is useful for design of metering mechanism for chickpea seeds.

#### COMPETING INTERESTS

Authors have declared that no competing interests exist.

#### REFERENCES

- Jadeja AS, Rajani AV, Kaneriya SC, Hirpara DV, Nutrient content, uptake, quality of chickpea (*Cicer arietinum* L.) and fertility status of soil as influenced by

fertilization of potassium and sulphur. Int. J. Curr. Microbiol. App. Sci. 2019;8(6): 2351-2355.

- Anonymous 2016. State concern Agriculture department, estimated area of 2015-16.
- Laxmikanth, Sushilendra, Veerangouda M, Vijayakumar Palled , Yadahalli GS, Study on physical properties of chickpea. Journal of Pharmacognosy and Phytochemistry. 2020;9(4): 511-514.
- Davies RM. Engineering properties of three varieties of melon seeds as potentials for development of melon processing machines. Advance Journal of Food Science and Technology. 2010; 2(1):63-66.
- Karaj S, Muller J. Determination of physical, mechanical and chemical properties of seeds and kernels of *Jatropha curcas* L. Industrial Crops and Products. 2010;1-10.
- Mollazade K, Ahmadi A, Khorshidi J, Rajabipour A, Mohtasebi SS. Moisture-dependent physical and mechanical properties of cumin (*Cuminum cyminum* L.) seed. Int. J. Agric. and Biol. Eng. 2009; 2(2):49-56.
- Sinha S, Verma A, Singh S, A study on some physical and engineering properties of the chickpea seeds. Int. J.Curr. Microbiol. App. Sci. 2019;8(11):1504-1509.
- Tavakoli H, Rajabipour A, Mohtasebi SS, , Moisture-dependent some engineering properties of soybean grains. Agricultural Engineering International: The CIGRE Journal. 2009;11(10):11-22.

9. Salah Ghamari, Khosro Mohammadi, chickpea seeds in kurdistan region of Iran. Abdolvahed Khanahmadzadeh, Hadi, Goli. International Journal of Agriculture and Forestry. 2014;4(3A):4-7. Evaluation the some physical properties of

© 2023 Veerammanavara et al.; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/4.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

*Peer-review history:*

*The peer review history for this paper can be accessed here:*  
<https://www.sdiarticle5.com/review-history/104991>